

## MODEL C85-2

### MINI CHEST ULTRA LOW FREEZER -40°C TO -85°C

|                                 |                              |
|---------------------------------|------------------------------|
| <b>Capacity [ Cu. Ft. ]</b>     | <b>2 Cu. Ft.</b>             |
| <b>Capacity [ Liters ]</b>      | <b>56 Liters</b>             |
| <b>Temperature Range [ °C ]</b> | <b>-40°C to -85°C</b>        |
| <b>Temperature Range [ °F ]</b> | <b>-40°F to -120°F</b>       |
| Dimensions                      | Width x Depth x Height       |
| Exterior [ Inches ]             | 22.25" x 25.75" x 40"        |
| Interior [ Inches ]             | 17" x 14" x 14"              |
| Exterior [ Centimeters ]        | 64 x 65 x 101                |
| Interior [ Centimeters ]        | 43 x 35 x 35                 |
| Refrigeration System            | Cascade-Style System         |
| Compressors                     | 2, Hermetic Compressors      |
| Air Circulation                 | Gravity Flow                 |
| Defrost Method                  | Manual                       |
| Refrigerant                     | HCFC & CFC Free              |
| Exterior                        | Powder Coated Steel          |
| Interior                        | Zinc Coated Galvanized Steel |
| Insulation                      | Polyurethane (Ecomate) Foam  |
| Additional Insulation           | Beaded Foam Sub-Lids         |
| Lockable Lid                    | Lockable with Padlock        |
| Porthole                        | Optional 1/2"                |
| Casters                         | 4, Swivel with Locks         |
| Storage                         | Base Shelf                   |
| Shipping Weight                 | 335 Lbs.                     |

#### Electrical

|                  |            |
|------------------|------------|
| Certification(s) | ETL Listed |
|------------------|------------|

#### Controller

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Display Type      | Microprocessor, Digital                         |
| Alarms            | High/Low Temp, Power Failure, Low Battery       |
| Alarm Relay       | Yes, Dry Contacts                               |
| Automatic Restart | Yes, Automatically Restarts After Power Failure |
| Backup Battery    | Yes, Only Powers Alarm                          |

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



**Warranty** 1 Year Parts & Labor