

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Substance name	: Acetone
Chemical name	: 2-Propanone
CAS-No.	: 67-64-1
Product code	: LC10420, LC10425
Formula	: C ₃ H ₆ O
Synonyms	: 2-propanone / beta-ketopropane / dimethyl formaldehyde / dimethyl ketone / dimethylketal / DMK (=dimethyl ketone) / keto propane / methyl ketone / pyroacetic acid / pyroacetic ether / pyroacetic spirit

1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Solvent Cleaning product Chemical raw material
Recommended use	: Laboratory chemicals
Restrictions on use	: Not for food, drug or household use

1.3. Supplier

LabChem, Inc.
1010 Jackson's Pointe Ct.
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 or +1-703-741-5970
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)	:  
Signal word (GHS US)	: Danger
Hazard statements (GHS US)	: H225 - Highly flammable liquid and vapor H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness
Precautionary statements (GHS US)	: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray, vapors.
P264 - Wash exposed skin thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Acetone (Main constituent)	CAS-No.: 67-64-1	100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms. After possible exposure, consult a doctor/medical service.

First-aid measures after inhalation : Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

First-aid measures after skin contact : If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact	: Rinse immediately with plenty of water. If irritation persists, consult a doctor/medical service.
First-aid measures after ingestion	: Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Nausea. Vomiting. Headache. Central nervous system depression. Dizziness. Narcosis. Excited/restless. Drunkenness. Disturbed motor response. Respiratory difficulties. Disturbances of consciousness.
Symptoms/effects after skin contact	: ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.
Symptoms/effects after eye contact	: Irritation of the eye tissue.
Symptoms/effects after ingestion	: Dry/sore throat. Gastrointestinal complaints. Risk of aspiration pneumonia. Symptoms similar to those listed under inhalation. AFTER ABSORPTION OF LARGE QUANTITIES: Irritation of the gastric/intestinal mucosa. Change in the blood composition. Change in urine output. Renal disease. Enlargement/disease of the liver.
Symptoms/effects upon intravenous administration	: Not available.
Chronic symptoms	: Red skin. Skin rash/inflammation. Dry/sore throat. Headache. Nausea. Feeling of weakness. Loss of weight. Possible inflammation of the respiratory tract.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (alcohol-resistant). Water spray if puddle cannot expand.
Unsuitable extinguishing media	: Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Specific hazards arising from the chemical

Fire hazard	: DIRECT FIRE HAZARD. Highly flammable liquid and vapour. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
Hazardous decomposition products in case of fire	: Upon combustion: CO and CO2 are formed.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.
Protection during firefighting	: Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Large spills/in enclosed spaces: self-contained breathing apparatus (EN 136 + EN 137). |
| Emergency procedures | : Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes. |

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. |
| Methods for cleaning up | : Take up liquid spill into inert absorbent material, e.g.: sand, earth, vermiculite. Scoop absorbed substance into closing containers. Spill must not return in its original container. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. |

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep container tightly closed. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|--|
| Storage conditions | : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Direct sunlight, incompatible materials. Keep container closed when not in use. |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. |
| Storage temperature | : 15 – 20 °C |
| Heat-ignition | : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources. |

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Prohibitions on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents. reducing agents. strong acids. (strong) bases. halogens. amines.
Storage area	: Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Keep container in a well-ventilated place. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.
Special rules on packaging	: SPECIAL REQUIREMENTS: closing. with pressure relief valve. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials	: SUITABLE MATERIAL: steel. stainless steel. carbon steel. aluminium. iron. copper. nickel. bronze. glass. MATERIAL TO AVOID: synthetic material.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA	594 mg/m ³
ACGIH OEL TWA [ppm]	250 ppm
ACGIH STEL (mg/m ³)	1187 mg/m ³
ACGIH STEL (ppm)	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	ACETONE
Biological Exposure Indices (BEI)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL (TWA) [1]	2400 mg/m ³
OSHA PEL (TWA) [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	2500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	590 mg/m ³
NIOSH REL TWA [ppm]	250 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls	: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.
----------------------------------	---

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Face shield. Chemical resistant apron.

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: butyl/viton. GIVE GOOD RESISTANCE: butyl rubber. tetrafluoroethylene. GIVE LESS RESISTANCE: chlorosulfonated polyethylene. natural rubber. Polyurethane. PVA. styrene-butadiene rubber. GIVE POOR RESISTANCE: polyethylene. PVC. viton. Nitrile rubber/PVC

Hand protection:

Protective gloves against chemicals (EN 374)

Eye protection:

Protective goggles (EN 166)

Skin and body protection:

Head/neck protection. Protective clothing (EN 14605 or EN 13034)

Respiratory protection:

Full face mask with filter type AX at conc. in air > exposure limit

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless
Odor	: Aromatic odour Sweet odour Fruity odour
Odor threshold	: No data available
pH	: 5 – 6 (20 °C)
Melting point	: -95 °C
Freezing point	: No data available
Boiling point	: 56 °C
Critical temperature	: 235 °C
Critical pressure	: 47010 hPa
Flash point	: -17 °C (Closed cup)
Relative evaporation rate (butyl acetate=1)	: 6
Relative evaporation rate (ether=1)	: 2
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: 240 hPa (20 °C)
Vapor pressure at 50 °C	: 828 hPa
Relative vapor density at 20 °C	: 2
Particle size	: Not applicable (liquid)
Relative density	: 0.79 (20 °C)
Relative density of saturated gas/air mixture	: 1.2

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Density	: 20 °C
Molecular mass	: 58.08 g/mol
Solubility	: Miscible with water. Soluble in ethanol. Soluble in ether. Soluble in dimethyl ether. Soluble in petroleum spirit. Soluble in chloroform. Soluble in dimethylformamide. Soluble in oils/fats. Water: miscible Ethanol: complete Ether: complete
Log Pow	: -0.23 (Test data)
Auto-ignition temperature	: 465 °C (T1)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available in the literature
Viscosity, dynamic	: 0.32 mPa·s (20 °C)
Explosion limits	: 2.15 – 13 vol % 60 – 310 g/m ³ Lower explosion limit: 2.15 vol % Upper explosion limit: 13 vol %
Explosive properties	: No data available.
Oxidizing properties	: None.

9.2. Other information

Minimum ignition energy	: 1.15 mJ
Specific conductivity	: 6000000 pS/m (25 °C)
Saturation concentration	: 589 g/m ³
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Highly volatile.

SECTION 10: Stability and reactivity

10.1. Reactivity

Violent to explosive reaction with many compounds. Prolonged storage: on exposure to light: release of harmful gases/vapours.

10.2. Chemical stability

Unstable on exposure to light.

10.3. Possibility of hazardous reactions

Reacts with (strong) oxidizers.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l (4 h, Rat, Female, Weight of evidence, Inhalation (vapours))
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (vapors)	76 mg/l/4h
ATE US (dust, mist)	76 mg/l/4h

Skin corrosion/irritation	: Not classified pH: 5 – 6 (20 °C)
Serious eye damage/irritation	: Causes serious eye irritation. pH: 5 – 6 (20 °C)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available in the literature
Likely routes of exposure	: Inhalation. Skin and eye contact.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Nausea. Vomiting. Headache. Central nervous system depression. Dizziness. Narcosis. Excited/restless. Drunkenness. Disturbed motor response. Respiratory difficulties. Disturbances of consciousness.
Symptoms/effects after skin contact	: ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.
Symptoms/effects after eye contact	: Irritation of the eye tissue.
Symptoms/effects after ingestion	: Dry/sore throat. Gastrointestinal complaints. Risk of aspiration pneumonia. Symptoms similar to those listed under inhalation. AFTER ABSORPTION OF LARGE QUANTITIES: Irritation of the gastric/intestinal mucosa. Change in the blood composition. Change in urine output. Renal disease. Enlargement/disease of the liver.
Symptoms/effects upon intravenous administration	: Not available.
Chronic symptoms	: Red skin. Skin rash/inflammation. Dry/sore throat. Headache. Nausea. Feeling of weakness. Loss of weight. Possible inflammation of the respiratory tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air	: Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water	: Not harmful to crustacea (Daphnia). Not harmful to fishes. Groundwater pollutant. Not harmful to activated sludge. Nitrification of activated sludge is inhibited. Slightly harmful to algae. Not harmful to plankton.

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

LC50 fish 1	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
-------------	---

12.2. Persistence and degradability

Acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.43 g O	□/g substance
Chemical oxygen demand (COD)	1.92 g O	□/g substance
ThOD	2.2 g O	□/g substance

12.3. Bioaccumulative potential

Acetone (67-64-1)

Log Pow	-0.23 (Test data)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Acetone (67-64-1)

Surface tension	23300 mN/m (20 °C)
Log Koc	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations	: Do not discharge into drains or the environment. Dispose of at authorized waste collection point. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA No	: UN1090
UN-No. (TDG)	: UN1090

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : 1090
UN-No. (IATA) : 1090

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Acetone
Proper Shipping Name (TDG) : ACETONE
Proper Shipping Name (IMDG) : acetone
Proper Shipping Name (IATA) : acetone

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3

TDG

Transport hazard class(es) (TDG) : 3
Hazard labels (TDG) : 3

IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1090
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No. (TDG) : UN1090
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Ship Index : Forbidden
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L

IMDG

Transport regulations (IMDG) : Subject to the provisions
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

IATA

Transport regulations (IATA) : Subject to the provisions

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Acetone (67-64-1)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Health hazard - Serious eye damage or eye irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Specific target organ toxicity (single or repeated exposure)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Acetone

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 09/30/2020

Other information : None.

Full text of H- and EUH-statements: see section 16

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: C - Safety glasses, Gloves, Synthetic apron

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.