

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Chloroform-Butanol Reagent
Product code : LC13050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Details of the supplier of the safety data sheet

LabChem Inc
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3	H226
Acute toxicity (oral) Category 4	H302
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2A	H319
Carcinogenicity Category 2	H351
Specific target organ toxicity (repeated exposure) Category 1	H372
Hazardous to the aquatic environment - Acute Hazard Category 2	H401

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer
H372 - Causes damage to organs (kidneys, liver, central nervous system, hearing organs) through prolonged or repeated exposure (Inhalation, oral)
H401 - Toxic to aquatic life

Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe mist, vapors, spray
P264 - Wash exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P330 - If swallowed, rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2) to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Chloroform	(CAS No) 67-66-3	84.6	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT RE 1, H372
1-Butanol	(CAS No) 71-36-3	15.4	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335 STOT RE 1, H372

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer (Inhalation).
First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes damage to organs (nervous system, kidneys, liver) through prolonged or repeated exposure (Ingestion, Inhalation).
Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.
Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.
Chronic symptoms : Cracking of the skin. Impaired concentration. Impaired memory.

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Combined gas/dust mask with filter type A/P3. Gloves. Protective clothing. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors, spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Ignition sources, incompatible materials. Keep container closed when not in use.
Incompatible products : Strong oxidizers.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Chloroform (67-66-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm (Chloroform; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
OSHA	OSHA PEL (Ceiling) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (Ceiling) (ppm)	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	9.78 mg/m ³ 60 min.
NIOSH	NIOSH REL (STEL) (ppm)	2 ppm 60 min.

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-Butanol (71-36-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (ceiling) (mg/m ³)	150 mg/m ³
NIOSH	NIOSH REL (ceiling) (ppm)	50 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Material should be handled in a laboratory hood whenever possible.
- Personal protective equipment : Gloves. Safety glasses.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Respiratory protection not required in normal conditions.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear, colorless liquid.
- Color : Colorless
- Odor : Sweet odour
- Odor threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : Non flammable.
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Relative density : No data available
- Specific gravity / density : 1.3 g/ml
- Solubility : Soluble in ethanol. Soluble in other organic solvents. Poorly soluble in water.
- Log Pow : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available

9.2. Other information

No additional information available

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Hydrogen chloride. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Oral: Harmful if swallowed.

Chloroform-Butanol Reagent	
LD50 oral rat	717 mg/kg
ATE US (oral)	717.000 mg/kg body weight

Chloroform (67-66-3)	
LD50 oral rat	695 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 908 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; 1117 mg/kg bodyweight; Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit; No reliable data available; >3980 mg/kg bodyweight; Rabbit)
ATE US (oral)	695.000 mg/kg body weight
ATE US (gases)	700.000 ppmV/4h
ATE US (vapors)	3.000 mg/l/4h
ATE US (dust, mist)	0.500 mg/l/4h

1-Butanol (71-36-3)	
LD50 oral rat	790 mg/kg
LD50 dermal rabbit	3400 mg/kg
LC50 inhalation rat (mg/l)	8 mg/l/4h
ATE US (oral)	790.000 mg/kg body weight
ATE US (dermal)	3400.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	8.000 mg/l/4h
ATE US (dust, mist)	8.000 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Chloroform (67-66-3)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Causes damage to organs (kidneys, liver, central nervous system, hearing organs) through prolonged or repeated exposure (Inhalation, oral).

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.
Chronic symptoms	: Cracking of the skin. Impaired concentration. Impaired memory.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life.

Chloroform (67-66-3)	
LC50 fish 1	18.2 ppm (LC50; ASTM; 96 h; Oncorhynchus mykiss; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	152.5 mg/l (EC50; US EPA; 48 h; Daphnia magna; Static system; Salt water; Experimental value)
1-Butanol (71-36-3)	
LC50 fish 1	1740 mg/l 96 hr., Pimephales promelas
EC50 Daphnia 1	1983 mg/l 48 hr., Daphnia magna
EC50 other aquatic organisms 1	500 mg/l 72 hr., Desmodesmus subspicatus

12.2. Persistence and degradability

Chloroform-Butanol Reagent	
Persistence and degradability	Not established.
Chloroform (67-66-3)	
Persistence and degradability	Not readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in soil.
ThOD	0.33 - 1.35 g O ₂ /g substance
BOD (% of ThOD)	0.015 - 0.06
1-Butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water. Not established.

12.3. Bioaccumulative potential

Chloroform-Butanol Reagent	
Bioaccumulative potential	Not established.
Chloroform (67-66-3)	
BCF fish 2	1.4 - 4.7 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value)
Log Pow	1.97 (Experimental value; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1-Butanol (71-36-3)	
Log Pow	0.88
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

12.4. Mobility in soil

Chloroform (67-66-3)	
Surface tension	0.0271 N/m (20 °C)
Log Koc	Koc, Other; 86.7-367; Experimental value; log Koc; Other; 1.94-2.56; Experimental value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2810 Toxic, liquids, organic, n.o.s., 6.1, III

UN-No.(DOT) : UN2810

Proper Shipping Name (DOT) : Toxic, liquids, organic, n.o.s.

Transport hazard class(es) (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 6.1 - Poison inhalation hazard



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 153

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Chloroform-Butanol Reagent

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chloroform	CAS No 67-66-3	84.6%
1-Butanol	CAS No 71-36-3	15.4%

Chloroform (67-66-3)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb
SARA Section 313 - Emission Reporting	0.1 %

1-Butanol (71-36-3)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard

15.2. International regulations

CANADA

Chloroform-Butanol Reagent

WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Chloroform (67-66-3)

Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

1-Butanol (71-36-3)

Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

National regulations

Chloroform (67-66-3)

Listed on the Canadian IDL (Ingredient Disclosure List)

1-Butanol (71-36-3)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

Chloroform (67-66-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	20 µg/day

SECTION 16: Other information

Revision date : 03/29/2017
Other information : None.

Chloroform-Butanol Reagent

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life

NFPA health hazard


: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS III Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: H
H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.