

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Eosin Y, 1% Alcoholic
Product code : LC14030

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem Inc
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or +1-703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids	H225	Highly flammable liquid and vapour
Category 2		
Acute toxicity (oral)	H302	Harmful if swallowed
Category 4		
Carcinogenicity Category	H350	May cause cancer (oral)
1A		
Reproductive toxicity	H361	Suspected of damaging the unborn child. (oral)
Category 2		
Specific target organ	H370	Causes damage to organs (central nervous system, optic nerve) (oral)
toxicity (single exposure)		
Category 1		

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapour
H302 - Harmful if swallowed
H350 - May cause cancer (oral)
H361 - Suspected of damaging the unborn child. (oral)
H370 - Causes damage to organs (central nervous system, optic nerve) (oral)

Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist, vapors, spray.
P264 - Wash exposed skin thoroughly after handling.

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, eye protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P311 - Call a POISON CENTER or doctor/physician.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO₂), extinguishing powder to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Ethanol	(CAS-No.) 64-17-5	89.3475	Flam. Liq. 2, H225 Carc. 1A, H350 Repr. 2, H361
Isopropyl Alcohol (2-Propanol)	(CAS-No.) 67-63-0	4.95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H335
Methanol	(CAS-No.) 67-56-1	4.7025	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
Eosin Y	(CAS-No.) 17372-87-1	1	Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Blindness. Central nervous system depression. Dizziness. Drunkenness. Nausea. Vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing mist, spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Do not breathe mist, vapors, spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Ignition sources, incompatible materials. Keep container tightly closed.
Incompatible products : Strong oxidizers.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)		
IDLH	US IDLH (ppm)	3300 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
Isopropyl Alcohol (2-Propanol) (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	400 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
IDLH	US IDLH (ppm)	2000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
Methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	250 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
NIOSH	Remark (NIOSH)	Skin
Eosin Y (17372-87-1)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses.



Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: nitrile rubber. GIVE POOR RESISTANCE: PVA

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Respiratory protection not required in normal conditions

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Green
Odor	: Alcohol odour
Odor threshold	: 100 ppm 188 mg/m ³
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: 2.4
Relative evaporation rate (ether=1)	: 8.3
Flammability (solid, gas)	: Flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: 1.6
Relative density	: No data available
Solubility	: Soluble in water. Soluble in ethanol.
Log Pow	: No data available
Auto-ignition temperature	: 363 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: 4.3 - 19 vol %
Explosive properties	: No data available.
Oxidizing properties	: None.

9.2. Other information

VOC content	: 60 %
-------------	--------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong oxidizers.

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Hydrogen bromide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Eosin Y, 1% Alcoholic	
ATE US (oral)	1683.502 mg/kg body weight
Ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit, Literature study)
LC50 inhalation rat (mg/l)	117 - 125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)
ATE US (oral)	10740 mg/kg body weight
Isopropyl Alcohol (2-Propanol) (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value)
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value)
LC50 inhalation rat (ppm)	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male/female, Experimental value)
ATE US (oral)	5045 mg/kg body weight
ATE US (dermal)	12870 mg/kg body weight
ATE US (vapors)	73 mg/l/4h
ATE US (dust, mist)	73 mg/l/4h
Methanol (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg body weight (BASF test, Rat, Male/female, Weight of evidence)
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data)
LC50 inhalation rat (mg/l)	128.2 mg/l air (BASF test, 4 h, Rat, Male/female, Weight of evidence)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Not classified
 Serious eye damage/irritation : Not classified
 Respiratory or skin sensitization : Not classified
 Germ cell mutagenicity : Not classified
 Carcinogenicity : May cause cancer (oral).

Reproductive toxicity : Suspected of damaging the unborn child. (oral).
 Specific target organ toxicity – single exposure : Causes damage to organs (central nervous system, optic nerve) (oral).

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if swallowed.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Blindness. Central nervous system depression. Dizziness. Drunkenness. Nausea. Vomiting.

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
Isopropyl Alcohol (2-Propanol) (67-63-0)	
LC50 fish 1	9640 - 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
ErC50 (algae)	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

Eosin Y, 1% Alcoholic	
Persistence and degradability	Not established.
Ethanol (64-17-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance
BOD (% of ThOD)	0.43
Isopropyl Alcohol (2-Propanol) (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance
Methanol (67-56-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
Eosin Y (17372-87-1)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Eosin Y, 1% Alcoholic	
Bioaccumulative potential	Not established.
Ethanol (64-17-5)	
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.
Isopropyl Alcohol (2-Propanol) (67-63-0)	
Log Pow	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Methanol (67-56-1)	
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
Log Pow	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Eosin Y (17372-87-1)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Ethanol (64-17-5)	
Surface tension	0.022 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Isopropyl Alcohol (2-Propanol) (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Ecology - soil	No (test) data on mobility of the substance available.
Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	-0.89 - -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1170 Ethanol solutions, 3, II

UN-No.(DOT) : UN1170

Proper Shipping Name (DOT) : Ethanol solutions

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 4b;150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Eosin Y, 1% Alcoholic	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Isopropyl Alcohol (2-Propanol)	CAS-No. 67-63-0	4.95%
Methanol	CAS-No. 67-56-1	4.703%

Isopropyl Alcohol (2-Propanol) (67-63-0)	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
Methanol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Acute toxicity (any route of exposure) Health hazard - Specific target organ toxicity (single or repeated exposure)

15.2. International regulations

CANADA

No additional information available

Methanol (67-56-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Eosin Y (17372-87-1)	
Listed on the Canadian DSL (Domestic Substances List)	

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Eosin Y (17372-87-1)

Not listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Eosin Y, 1% Alcoholic

U.S. - California - Proposition 65 - Carcinogens List	No
---	----

U.S. - California - Proposition 65 - Developmental Toxicity	Yes
---	-----

U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
---	----

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

SECTION 16: Other information

Revision date : 05/16/2018

Other information : None.


Full text of H-phrases: see section 16:

H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs

Eosin Y, 1% Alcoholic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.	
NFPA fire hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.	
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.	
Hazard Rating		
Health	: 2 Moderate Hazard - Temporary or minor injury may occur	
Flammability	: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)	
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	
Personal protection	: G G - Safety glasses, Gloves, Vapor respirator	

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.