

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)
Product code : LC17670

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem Inc
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Corrosive to metals	H290	May be corrosive to metals
Category 1		
Skin corrosion/irritation	H314	Causes severe skin burns and eye damage
Category 1B		
Serious eye damage/eye irritation	H318	Causes serious eye damage
Category 1		
Respiratory sensitization,	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
Category 1		
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Carcinogenicity Category 1A	H350	May cause cancer
Reproductive toxicity	H360	May damage fertility or the unborn child
Category 1B		

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

- H290 - May be corrosive to metals
- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H350 - May cause cancer
- H360 - May damage fertility or the unborn child

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P234 - Keep only in original container
- P260 - Do not breathe mist
- If inhaled: Remove person to fresh air and keep comfortable for breathing
- P264 - Wash exposed skin thoroughly after handling

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P284 - Wear respiratory protection
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor/physician
P363 - Wash contaminated clothing before reuse
P390 - Absorb spillage to prevent material damage
P405 - Store locked up
P406 - Store in corrosive resistant container with a resistant inner liner
P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS-No.) 7732-18-5	95.76	Not classified
Nitric Acid, 70% w/w	(CAS-No.) 7697-37-2	3.74	Ox. Liq. 3, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Nickel (II) Nitrate Hexahydrate	(CAS-No.) 13478-00-7	0.5	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350 Repr. 1B, H360 STOT SE 3, H335 STOT RE 1, H372

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage. May damage fertility or the unborn child.

Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation.

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage.

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : Burns. Nausea. Vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Reactivity : Thermal decomposition generates : Corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves. Face-shield.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use.

Incompatible products : Strong bases. Strong oxidizers. Strong reducing agents. metals. organic materials.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nickel (II) Nitrate Hexahydrate (13478-00-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.1 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	0.1 mg/m ³
IDLH	US IDLH (mg/m ³)	10 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.015 mg/m ³

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitric Acid, 70% w/w (7697-37-2)		
ACGIH	ACGIH TWA (ppm)	2 ppm (Nitric acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	4 ppm (Nitric acid; USA; Short time value; TLV - Adopted Value)
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	2 ppm
IDLH	US IDLH (ppm)	25 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	2 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)	4 ppm
Water (7732-18-5)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Chemical resistant apron. Face shield. Gloves. Protective clothing. Safety glasses.



Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Gas mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Green
Odor	: None.
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.02 g/ml
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 0.99 cSt
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers. Strong bases. Strong reducing agents. Organic compounds. metals.

10.6. Hazardous decomposition products

Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact

Acute toxicity : Not classified

Nickel (II) Nitrate Hexahydrate (13478-00-7)	
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nickel (II) Nitrate Hexahydrate (13478-00-7)	
IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Burns. Nausea. Vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Nitric Acid, 70% w/w (7697-37-2)	
EC50 Daphnia 1	180 mg/l (EC50; 48 h)
LC50 fish 2	72 ppm (LC50; 96 h)
Threshold limit algae 1	> 19 mg/l (EC0)

12.2. Persistence and degradability

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)	
Persistence and degradability	Not established.
Nitric Acid, 70% w/w (7697-37-2)	
Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Water (7732-18-5)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)	
Bioaccumulative potential	Not established.
Nitric Acid, 70% w/w (7697-37-2)	
BCF fish 1	<= 1 (BCF)
Log Pow	-2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Bioaccumulation: not applicable.
Water (7732-18-5)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
------------------------------	---------------------------------------

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GWPmix comment	: No known effects from this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid), 8, II

UN-No.(DOT)	: UN3264
Proper Shipping Name (DOT)	: Corrosive liquid, acidic, inorganic, n.o.s.
Transport hazard class(es) (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Nickel (II) Nitrate Hexahydrate	CAS-No. 13478-00-7	0.5%
---------------------------------	--------------------	------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Nickel (II) Nitrate Hexahydrate	CAS-No. 13478-00-7	0.5%
Nitric Acid, 70% w/w	CAS-No. 7697-37-2	3.74%

Nickel (II) Nitrate Hexahydrate (13478-00-7)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Reactive hazard
-------------------------------------	---

Nitric Acid, 70% w/w (7697-37-2)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

Nickel (II) Nitrate Hexahydrate (13478-00-7)

Not listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Revision date	: 01/10/2018
Other information	: None.

Nickel AA Standard, 1000 ppm (1mL = 1mg Ni)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

NFPA health hazard


: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability

: 0 Minimal Hazard - Materials that will not burn

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: H

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.