

Labmax™ Bottle Top Dispensers

The Labmax Bottle Top Dispensers offers the ultimate in dispensing convenience. An air purging system conveniently dispenses any air prior to dispensing media. A safety shutdown position eliminates dripping and accidental dispensing. An integrated swivel neck allows dispensing in any direction without affecting the fit of the dispenser on the bottle threads. Volume adjustment is quick and easy with the locking turn knob. The direct displacement glass piston fully dispenses the reagent with each stroke, ensuring accuracy and eliminating sticking and freezing caused by excess reagent remaining in the reservoir.

The Labmax is fully autoclavable and is easily disassembled for cleaning. The standard Labmax is available in six volume ranges. A glass piston and cylinder allow for compatibility with most common reagents and organic solvents. A PTFE piston and cylinder version is available for use with HF.

Features

- ▶ Factory calibrated to strict ISO 8655 standard
- ▶ User-friendly in-lab recalibration system, calibration tool provided with every dispenser
- ▶ 360° rotatable valve block for work convenience
- ▶ Set of thread adapters provided with every dispenser
- ▶ 1-year warranty



Ordering Information

Cat. No.	Volume Range (mL)	Accuracy (mL)	Tolerance (mL)	Thread (mm)
D5370-2	0.3-2.5	0.05	0.02	33**
D5370-5	1-5	0.10	0.04	33**
D5370-10	2-10	0.20	0.08	33**
D5370-10HF*	2-10	0.20	0.08	33**
D5370-25	5-25	0.50	0.15	45***
D5370-25HF*	5-25	0.50	0.15	45***
D5370-50	10-50	1.00	0.40	45***
D5370-100	20-100	2.00	0.80	45***

*HF = PTFE piston and cylinder version for HF and other aggressive solvents

**Supplied with 24, 28, 38, and 45 mm adapters

***Supplied with 28, 33, and 38 mm adapters

Accessories

Cat. No.	Description
D5375-002	Extended discharge tube, fits 2, 5, and 10 mL bottle top dispensers
D5375-012	Extended discharge tube, fits 25, 50, and 100 mL bottle top dispensers
D5377-310	Calcium chloride drying tube, fits all Labmax bottle top dispensers