

Product Name:	CRT-ABT-HC-S23S
Description:	Upright Controlled Room Temperature Cabinet, Solid Door 23 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle 2 probes; 1 in air and 1 in sample bottle Four adjustable shelves (adjustable in ½” increments) Vaccine storage power cord warning label Forced draft air circulation LED interior lights are safety shielded and switch controlled Swivel Casters (3”) Probe access port (⅜”) White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 26 ⅞” W x 34 ¾” D x 81 ¾” H with casters; 78 ¼” H without casters Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP UL/C-UL listed Shipping weight: 250 lbs.