

Product Name:	CRT-ABT-HC-S26S
Description:	Upright Controlled Room Temperature Cabinet, Solid Door 26 Cu. Ft. capacity One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm 2 probes; 1 in air and 1 in sample bottle Four adjustable shelves Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel Casters (3") Probe access port ($\frac{3}{8}$") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 28 $\frac{3}{8}$" W x 36 $\frac{1}{2}$" D x 81 $\frac{3}{4}$" H with casters; 78 $\frac{1}{4}$" H without casters Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP ETL listed Shipping weight: 275 lbs.